

COACH MASTER

	Tire Size	Star Rating	Load Index	TRA Code	Tread Depth (mm)	Type	Rim Standard (RIM WIDTH&FLANGE)	(mm)		Max Load (kg)	Standard Pressure (bar)	Max speed (km/h)
								Diameter	Section Width			
CM01N	17. 5R25	★★	182/167	L-3/E-3	28	TL	14. 00/1. 5	1348	445	8500/5450	6. 5/5. 25	10/50
	20. 5R25	★★	193/177	L-3/E-3	31	TL	17. 00/2. 0	1490	521	11500/7300	6. 5/5. 25	10/50
	23. 5R25	★★	201/185	L-3/E-3	34	TL	19. 50/2. 5	1617	597	14500/9250	6. 5/5. 25	10/50
	26. 5R25	★★	209/193	L-3/E-3	37	TL	22. 00/3. 0	1750	673	18500/11500	6. 5/5. 25	10/50
	17. 5R25	★★	182	TL	TL	TL	14. 00-1. 5	1348	445	8500	6. 5	10
	20. 5R25	★★	193	L-3	28. 5	TL	17. 00-2. 0	1490	521	11500	6. 5	10
	23. 5R25	★★	201	L-3	31. 5	TL	19. 50-2. 5	1617	597	14500	6. 5	10
	26. 5R25	★★	209	L-3	34. 5	TL	22. 00-3. 0	1750	673	18500	6. 5	10
CM02N	23. 5R25	★★	201	L-3	32	TL	19. 50/2. 5	1617	597	14500	6. 5	10
	23. 5R25	★★	201/185	L-3/E-3	34	TL	19. 50/2. 5	1617	597	14500/9250	6. 5/5. 25	10/50
	26. 5R25	★★	209/193	L-3/E-3	37	TL	22. 00/3. 0	1750	673	18500/1500	5. 25/4. 5	10/50
	29. 5R25	★★	216/200	L-3/E-3	43. 5	TL	25. 00/3. 5	1873	750	22400/14000	6. 5/5. 25	10/50
	29. 5R29	★★	218/202	L-3/E-3	43. 5	TL	25. 00/3. 5	1975	750	23600/15000	6. 5/5. 25	10/50
CM02S	600/65R25	★★	187/178	L-3/E-3	35. 5	TL	19. 50-2. 5	1415	606	9750/7500	4. 75/4. 25	10/50
	650/65R25	★★	193/180	L-3/E-3	38. 5	TL	19. 50-2. 5	1480	640	11500/8000	4. 75/4. 25	10/50
	750/65R25	★★	202/190	L-3/E-3	44. 5	TL	24. 00-3. 0	1599	738	15000/10600	4. 75/4. 25	10/50
	850/65R25	★★	207/196	L-3/E-3	48. 5	TL	27. 00-3. 5	1740	852	17500/12500	4. 75/4. 25	10/50
	875/65R29	★★	214/203	L-3/E-3	52. 5	TL	28. 00-3. 5	1881	883	21200/15500	4. 75/4. 25	10/50
	16. 00R25	★★	177B	E-4	46	TL	11. 25-2. 0	1532	445	7300	7	50

COACH MASTER

	Tire Size	Star Rating	Load Index	TRA Code	Tread Depth (mm)	Type	Rim Standard (RIM WIDTH&FLANGE)	(mm)		Max Load (kg)	Standard Pressure (bar)	Max speed (km/h)
								Diameter	Section Width			
CM03S	14. 00R24	★★★	168	E-4	38	TL	10. 0	1418	383	6050	7. 5	50
	14. 00R25	★★★	168	E-4	38	TL	10. 00/1. 5	1418	383	6050	8	50
	18. 00R25	★★	185	E-4	47	TL	13. 00/2. 5	1673	498	9250	7	50
CM04S	18. 00R33	★★	191	E-4	54	TL	13. 00/2. 5	1877	498	10900	7	50
	21. 00R35	★★	201	E-4	61	TL	15. 00/3. 0	2052	572	14500	7	50
	24. 00R35	★★	209	E-4	68	TL	17. 00/3. 5	2175	653	18500	7	50
CM04S2	18. 00R33	★★	191	E-4	49	TL	13. 00/2. 5	1877	498	10900	7	50
	21. 00R35	★★	201	E-4	52	TL	15. 00/3. 0	2052	572	14500	7	50
	24. 00R35	★★	209	E-4	58	TL	17. 00/3. 5	2175	653	18500	7	50
CM05N	14. 00R24 (385/95R24)	★★★	170	E-2	23	TT	10. 00W	1356	382	6000	10	70
	14. 00R25 (385/95R25)	★★★	170	E-2	23	TL	10. 00/1. 5	1356	382	6000	10	70
	16. 00R25 (445/95R25)	★★★	174	E-2	28	TL	11. 25/2. 0	1493	432	6700	10	80
	17. 5R25 (445/80R25)	★★★	170	E-2	28	TL	14. 00/1. 5	1348	445	6000	10	70
	20. 5R25 (525/80R25)	★★★	179	E-2	31	TL	17. 00/2. 0	1490	521	7750	10	70
	18. 00R25 (505/95R25)	★★★	186	E-2	28	TL	13. 00/2. 5	1615	498	9500	10	70
	14. 00R24 (385/95R24)	★★★	170	E-2	23	TL	10. 00W	1368	382	6000	10	70

COACH MASTER

	Tire Size	Star Rating	Load Index	TRA Code	Tread Depth (mm)	Type	Rim Standard (RIM WIDTH&FLANGE)	(mm)		Max Load (kg)	Standard Pressure (bar)	Max speed (km/h)
								Diameter	Section Width			
CMGZN	14. 00R25 (385/95R25)	★★★	170	E-2	23	TL	10. 00/1. 5	1368	382	6000	10	70
	16. 00R25 (445/95R25)	★★★	174	E-2	28	TL	11. 25/2. 0	1493	432	6700	10	80
CM06S	18. 00R25	★★	185	E-4	47	TL	13. 00/2. 5	1673	498	9250	7	50
	18. 00R33	★★	191	E-4	49	TL	13. 00/2. 5	1877	498	10900	7	50
	21. 00R33	★★	200	E-4	54	TL	15. 00/3. 0		570	2000	7	50
CMWYN	15. 5R25	★★	176/160	L-2/E-2	25	TL	12. 00/1. 3	1277	394	7100/4500	6. 5/5. 25	10/50
	17. 5R25	★★	182/167	L-2/E-2	28	TL	14. 00/1. 5	1348	445	8500/5450	6. 5/5. 25	10/50

COACH MASTER

	Tire Size	Star Rating	Load Index	TRA Code	Tread Depth (mm)	Type	Rim Standard (RIM WIDTH&FLANGE)	(mm)		Max Load (kg)	Standard Pressure (bar)	Max speed (km/h)
								Diameter	Section Width			
CMWYN	20. 5R25	★★	193/177	L-2/E-2	31	TL	17. 00/2. 0	1490	521	11500/7300	6. 5/5. 25	10/50
	23. 5R25	★★	201/185	L-2/E-2	34	TL	19. 50/2. 5	1617	597	14500/9250	6. 5/5. 25	10/50
	26. 5R25	★★	209/193	L-2/E-2	37	TL	22. 00/3. 0	1750	673	18500/11500	6. 5/5. 25	10/50
	29. 5R25	★★	216/200	L-2/E-2	43. 5	TL	25. 00/3. 5	1873	750	22400/14000	6. 5/5. 25	10/50
	16. 00R25	★★★	179	E-2	28	TL	11. 25/2. 0	1493	432	6700	10	70
CMXDN	17. 5R25	★★	182/167	L-3/E-3	28	TL	14. 00/1. 5	1348	445	8500/5450	6. 5/5. 25	10/50
	20. 5R25	★★	193/177	L-3/E-3	31	TL	17. 00/2. 0	1490	521	11500/7300	6. 5/5. 25	10/50
	23. 5R25	★★	201/185	L-3/E-3	42. 5	TL	19. 50/2. 5	1617	597	14500/9250	6. 5/5. 25	10/50
	26. 5R25	★★	209/193	L-3/E-3	45	TL	22. 00/3. 0	1750	673	18500/11500	6. 5/5. 25	10/50
	29. 5R25	★★	216/200	L-3/E-3	48	TL	25. 00/3. 5	1873	750	22400/14000	6. 5/5. 25	10/50
CMDTS	23. 5R25	★★	185	E-4	48	TL	19. 50/2. 5	1673	597	9250	5. 25	50
	26. 5R25	★★	193	E-4	52	TL	22. 00/3. 0	1798	673	11500	5. 25	50
	29. 5R25	★★	200	E-4	57	TL	25. 00/3. 5	1921	750	14000	5. 25	50
	29. 5R29	★★	202	E-4	57	TL	25. 00/3. 5	2023	750	15000	5. 25	50
CMDRS	18. 00R33	★★	191	E-4	54	TL	13. 00/2. 5	1877	498	10900	7	50
	21. 00R35	★★	201	E-4	54	TL	15. 00/3. 0	2052	572	14500	7	50
	24. 00R35	★★	209	E-4	58	TL	17. 00/3. 5	2160	653	18500	7	50
CMGDN	12. 00R24	★★★	152	E-3	30	TT	8. 5	1225	315			50
CMGXN	14. 00R25	★★★	168	E-3	33	TL	10. 00/2. 0 10. 00/1. 5	1370	370	6050	8	50

COACH MASTER

	Tire Size	Star Rating	Load Index	TRA Code	Tread Depth (mm)	Type	Rim Standard (RIM WIDTH&FLANGE)	(mm)		Max Load (kg)	Standard Pressure (bar)	Max speed (km/h)
								Diameter	Section Width			
CMOFN	13. 00R25	★★★	167	E-3	28	TL	8.5	1300	330	5450	8.25	50
	14. 00R24	★★★	168	E-3	28	TL	10.0	1370	370	6050	7.5	50
	14. 00R25	★★★	168	E-3	28	TL	10.00/2.0 10.00/1.5	1370	370	6050	8	50
CMN609	13. 00R25	★★★	167	E-3	26	TL	8.5	1300	330	5450	8.25	50
CMLGH	16. 00R24	★★	163	L-2/G-2	27	TL	10.00	1459	427	4875	3.75	10/40
CMWS+/CMWS	17. 5R25	★★	182	L-5	68	TL	14.00/1.5	1399	445	8500	6.5	10
	20. 5R25	★★	193	L-5	78	TL	17.00/2.0	1548	521	11500	6.5	10
	23. 5R25	★★	201	L-5/L-4	87/51	TL	19.50/2.5	1673	597	14500	6.5	10
	26. 5R25	★★	209	L-5/L-4	96/60	TL	22.00/3.0	1798	673	18500	6.5	10
	29. 5R25	★★	216	L-5/L-4	104/66	TL	25.00/3.5	1921	750	22400	6.5	10
	29. 5R29	★★	218	L-5	104	TL	25.00/3.5	2023	750	23600	6.5	10
	35/65R33	★★	224	L-5/L-4	97/62.5	TL	28.00/3.5	2077	889	28000	6.5	10
CMWS2+	20. 5R25	★★	193	L-5	68	TL	17.00/2.0	1548	521	11500	6.5	10
	23. 5R25	★★	201	L-5	75	TL	19.50/2.5	1673	597	14500	6.5	10
	26. 5R25	★★	209	L-5	85	TL	22.00/3.0	1798	673	18500	6.5	10
	29. 5R25	★★	216	L-5	90	TL	25.00/3.5	1921	750	22400	6.5	10
	12. 00R24	★★	175	L-5	55	TL	8.50-1.3	1135	315	6150	8.25	10
	17. 5R25	★★	182	L-5	65	TL	14.00/1.5	1399	445	8500	6.5	10
	20. 5R25	★★	193	L-5	72	TL	17.00/2.0	1548	521	11500	6.5	10

COACH MASTER

	Tire Size	Star Rating	Load Index	TRA Code	Tread Depth (mm)	Type	Standard Rim (RIM WIDTH&FLANGE)	(mm)		Max Load (kg)	Standard Pressure (bar)	Max speed (km/h)
								Diameter	Section Width			
CMS+	23.5R25	★★	201	L-5	83	TL	19.50/2.5	1673	597	14500	6.5	10
	26.5R25	★★	209	L-5	90	TL	22.00/3.0	1798	673	18500	6.5	10
	29.5R25	★★	216	L-5	100	TL	25.00/3.5	1921	750	22400	6.5	10
	29.5R29	★★	218	L-5	100	TL	25.00/3.5	2023	750	23600	6.5	10
	18.00R25	★★	204	L-5	80	TL	13.00/2.5	1655	515	16000	8.25	10
	35/65R33	★★	224	L-5	97	TL	28.00/3.5	2050	895	28000	6.5	10
CMCHS+ / CMCHS	23.5R25	★★	201/185	L-4/E-4	47	TL	19.50/2.5	1673	597	14500/9250	6.5/5.25	10/50
	26.5R25	★★	209/193	L-4/E-4	57	TL	22.00/3.0	1798	673	18500/11500	6.5/5.25	10/50
	29.5R29	★★	218/202	L-4/E-4	60	TL	25.00/3.5	2023	750	23600/15000	6.5/5.25	10/50
	35/65R33	★★	224/207	L-4/E-4	62.5	TL	28.00/3.5	2075	880	28000/17500	6.5/5.25	10/50

COACH MASTER

	Tire Size	Star Rating	Load Index	TRA Code	Tread Depth (mm)	Type	Rim Standard (RIM WIDTH&FLANGE)	(mm)		Max Load (kg)	Standard Pressure (bar)	Max speed (km/h)
								Diameter	Section Width			
CMCHS+ / CMCHS	20. 5R25	★★	193	L-5	72	TL	17. 00/2. 0	1548	521	11500	6. 5	10
	23. 5R25	★★	201	L-5	78	TL	19. 50/2. 5	1673	597	14500	6. 5	10
	26. 5R25	★★	209	L-5	87	TL	22. 00/3. 0	1798	673	18500	6. 5	10
	29. 5R25	★★	216	L-5	95	TL	25. 00/3. 5	1921	750	22400	6. 5	10
	29. 5R29	★★	218	L-5	95	TL	25. 00/3. 5	2023	750	23600	6. 5	10
	35/65R33	★★	224	L-5	97	TL	28. 00/3. 5	2075	880	28000	6. 5	10
CM08S	12. 00R24	★★★★	178	IND-4	41. 5	TL	8. 5	1245	340	7500	10	25
	16. 00R25	★★★★	200	IND-4	72. 5	TL	11. 25/2. 0	1530	430	14000	10	25
	18. 00R25	★★★★	214	IND-4	63	TL	13. 00/2. 5	1680	510	21200	10	25
	18. 00R33	★★★★	219	IND-4	73	TL	13. 00/2. 5	1860	510	24300	10	25
CM07S	18. 00R25	★★★★	214	IND-4	63	TL	13. 00/2. 5	1680	510	21200	10	25
CM03	27. 00R49	★★	223	E-4	61	TL	19. 50/4. 0	2702	737	27250	7. 0	50
CM06	30. 00R51	★★	230	E-4	64	TL	22. 00/4. 5	2904	823	33500	7. 0	50
CM06	30. 00R51	★★	230	E-4	64	TL	22. 00/4. 5	2904	823	33500	7. 0	50
CM06	33. 00R51	★★	235	E-4	70	TL	24. 00/5. 0	3061	894	38750	7. 0	50
CM06	36. 00R51	★★	241	E-4	78	TL	26. 00/5. 0	3233	988	46250	7. 0	50